



Characteristics	Luxury RigidCore Plank Floating Floor with IXPE Underlayment and Superior click system
Description	Plank Size 7" Wide x 48" Long
Size / Thickness	4.7mm Total Thickness (3.7mm Core + 1.0mm EVA + 0.3mm Wearlayer)
Installation	Click System - Floating
Warranty	Lifetime Residential Wear Warranty Lifetime Structural Warranty Limited Lifetime Waterproof Warranty 10 Year Limited Light Commercial Warranty
Heat Resistance & Color Stability	ISO 23999 - Final Curl Avg 0.37mm ASTM F1514 - After 7 days of accelerated heat in the chamber, No Change occurred.
Color Change - Light Stability	ASTM F1515 - 100-300 Hours Direct accelerated light - Resulting in nearly No Change
Impact Resistance	ASTM F1914 - 0.002" after 60min recovery time - Surface Integrity - No puncture through wear layer
Static Load Limit	ASTM F970 - Results 0.002" - Exceeding Classification (34) requirements
Castor Chair Resistance	Classification (34) No visible damage effects from furniture leg testing.
Approximate IIC Rating on 6" Thick Concrete Slab Floor (150 lbs/cu ft)	IIC: 59
Resistance to Chemical	ASTM F925 - No change occurred to product after exposure
Fire Rating	ASTM E648 - Results "Exceeds Class 1 rating as specified in NFPA Life Safety Code 101
Peel Strenth ISO 24345:2006	Mean Value: MD 110 N/50mm; AMD 105 N/50mm
Fungi Resistance ASTM G21-15	Unlike Cork, this product shows zero "None" results for observed growth.
FloorScore®	SCS-FS-04026   2016.06.01 - 2017.05.31
Packaging	
Content of Box	(7" x 48" - 21.27Sq.Ft./ Box )